

NICOPRESS Aluminum Oval Sleeves



FOR STEEL AIRCRAFT CONTROL CABLE & WIRE ROPE													
NICOPRESS OVAL SLEEVES					NICOPRESS APPLICATION TOOL SELECTION								
CABLE SIZE		OVAL SLEEVE	APPROX WT (PER 1000/M)		HAND TOOLS		BENCH TOOL HEAD		HYDRAULIC TOOLS		AT-PNEUMATIC	BATTERY TOOLS	
in	mm	ALUMINUM	lb	kg	SINGLE-GROOVE	MULTI-GROOVE	SINGLE-GROOVE	MULTI-GROOVE	3512 DIE	635 DIE	POWER HEAD	5606 DIE	5512 & 5612 DIES
3/64	1	188-1.5 VB4	0.7	0.3	31-B4 51-B4-887	17-B4B 33V-CGB4	51-B4-887 HEAD		12-OVAL-B4	OVAL-B4	AT-B4	6-188-B4	12-OVAL-B4
1/16	1.5	188-2-VC	1	0.4	51-C-887 3-C-887	33V-CGB4 32-VC-VG 64-CGMP* 3V-CGMP	51-C-887 HEAD 3-C-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD	12-OVAL-C	OVAL C	AT-C AT-CGMP	6-188-C	12-OVAL-C
3/32	2-2.5	188-3-VG	2.8	1.3	51-G-887 3-G-887	33V-CGB4 32-VC-VG 64-CGMP*	51-G-887 HEAD 3-G-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD	12-188-VG	188-VG	AT-G AT-CGMP	6-188-G	12-188-VG
1/8	3-3.5	188-4-VM	6.1	2.8	51-M-850	64-CGMP* 63V-XPM* 51-MJ 3V-F6:X:M 3-MJ 3V-CGMP	51-M-850 HEAD 3-M-850 HEAD	64-CGMP HEAD 63V-XPM HEAD 51-MJ HEAD 3V-CGMP HEAD 3V-F6:X:M HEAD 3-MJ HEAD	12-188-VM	188-VM	AT-M AT-CGMP AT-XPM AT-MJ	6-188-M	12-188-VM
5/32	4	188-5-VP	9	4	51-P-850	64-CGMP* 63V-XPM* 3V-CGMP	51-850 HEAD 3-P-850 HEAD	64-CGMP HEAD 63V-XPM HEAD 3V-CGMP HEAD	12-188-VP	188-VP	AT-P AT-CGMP AT-XPM	6-188-P	12-188-VP
3/16	5	188-6-VX	16	7	51-X-850	63-V-XPM* 3V-F6:X:M	51-X-850 HEAD 3-X-850 HEAD	63V-XPM HEAD 3V-F6:X:M HEAD	12-188-VX	188-VX	AT-X AT-XPM AT-X-F6**	6-188-VX	12-188-VX
1/4	-	188-8-VF6	27	12	3-F6-950	3V-F6:X:M	3-F6-950 HEAD	3V-F6:X:M HEAD	12-188-VF6	188-VF6	AT-F6** AT-X-F6**	6-188-F6	12-188-F6
9/32	7	188-9-VG2	30	13.6	3-G2-950		3-G2-950 HEAD		12-VG-2	VG-2	AT-G2**		
5/16	8	188-10-VG92	48	22	3-G9-950		3-G9-950 HEAD		12-VG92	VG-92	AT-G9**	6-188-VG9	12-VG92
3/8	9	188-12-VH5	65	47	3-H5-950		3-H5-950 HEAD		12-OVAL-H5	OVAL H5			12-OVAL-H5
7/16	10-11	188-14-VK8	115	52					12-OVAL-K8	OVAL K8			12-OVAL-K8
1/2	-	188-16-VM1	172	78					12-188-VM1	188-VM1			

*Model also available with cable cutter. Specify 64-CGMP/cutter tool or 63V-XPM/cutter tool.
 **Must be crimped using accessory booster kit.